

PROFELM ELECTRONICS A.B.E.E.

Λεωφ Αμφιθέας 185, 175 63 Παλ. Φάληρο <http://www.profelm.com>
τηλ : (210) 985 0144, fax : (210) 9850143, [e-mail: info@profelm.gr](mailto:info@profelm.gr)



Motherboard	<p>CPU Intel Core2 Duo, Core2 Quad, Pentium Dual-Core, Celeron Dual-Core, or Celeron 4xx processor (Socket 775)</p> <p>System Freq. 800/1066/1333/1600 MHz</p> <p>Memory Two 240-PIN DDRII DIMM up to 4GB Max. (Support DDRII 677/800 and Dual Channel Mode)</p> <p>Video Integrated GMA3100 with Max. 256MB Shared Video</p> <p>Memory</p> <p>Ethernet Onboard 10/100Mbps Ethernet</p> <p>Audio AC97 Codec Audio Subsystem</p>
Device HDD	2.5" or 3.5" IDE/SATA x 1 (Support Ultra DMA 100)
I/O Connector	<p>Serial Port x 1 + 2 Optional Parallel Port x 1 USB 2.0 Port x 4 (External) + 4 (Internal) PS/2 Mini-DIN Keyboard Port x 1 PS/2 Mini-DIN Mouse Port x 1 RJ-45 Ethernet Port x 1 Audio Line-in/Line-out/Mic-in Jack x 1 Set # Available Serial & USB port may be different according to interface of touch panel and integrated optional devices.</p>
Monitor	17" XGA TFT LCD
Touch Screen	TW 5-wire or ELO Resistive Touch Screen (RS-232 or USB Interface)
Power Supply	Internal Power Supply
Optical Integrated Device	VFD Customer Display, MSR Card Reader, Fingerprint Scanner 3-in-1 MSR + Smartcard + i-Button Reader
Dimension (mm)	418(W) x 241(H) x 357(D)

Λεωφ. Αμφιθέας 185, 175 63 Παλ. Φάληρο <http://www.profelm.com>
τηλ : (210) 985 0144, fax : (210) 985 0143, [e-mail: info@profelm.gr](mailto:info@profelm.gr)